



Specifications

Model	ATN-171MKP+2N-KVM8 PS2	
17 Inch LCD	1280x1024	
White Luminance (Center)	250 [cd/m2] (Typ.)	
Contrast Ratio	1000 : 1 (Typ.)	
KVM port number	8	
KVM port interface	Screen/keyboard/mouse	Monitor: D-Sub 15, Keyboard: PS/2, Mouse: PS/2
Control port interface	Screen	HDB-15 (Female)
	Keyboard	6 pin mini-DIN (Female) , USB Type A (Female)
	Mouse	6 pin mini-DIN (Female) , USB Type A (Female)
Support platform	DOS、 Windows、 Linux、 FreeBSD、 Mac、 Sun Micro System	
Button panel	Two-color light signals/independent press (8)	
LED lights	Green light: computers powered on; yellow light: switch computers status	
Toggle	Button panel, keyboard hotkey, OSD control menu	
Depending on the control display (OSD)	Built-in (intelligent machines)	
Auto scan interval	1 ~ 255 Seconds	
Operating temperature range	0° ~ 50°C	
Operating humidity range	0 ~ 80% RH	
Material	Metal shell (black)	
Weight	13300g	
Dimensions (LxWxH)	618.5x482.6x44.5 mm	
Carton Dimension	72x57x16	



Outline Dimensions

Unit: mm

